

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Jacksonville District		SHEET 1 OF 1	
1. PROJECT DADE COUNTY SPP				10. SIZE AND TYPE OF BIT 3 1/2" Drive Shoe			
2. LOCATION (Coordinates or Station) X=79769.8.4 Y=48986.2.9				11. DATUM FOR ELEVATION SHOWN (TBM or NSL) MLW			
3. DRILLING AGENCY ALPINE OCEAN SURVEY, INC.				12. MANUFACTURER'S DESIGNATION OF DRILL VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) CB-DAC-179				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER NICK PRICE				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER Tide = +3.3			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 7/4/98 1104			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -32.9 Ft.			
9. TOTAL DEPTH OF HOLE 19.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF GEOLOGIST ROCKLAND BURR			
ELEV.	DEPTH	LOG	CLASSIFICATION OF MATERIALS (Description)	CORE REC. %	SAMPLE NUMBER	REMARKS	
-32.9	0					-32.9	0
			Sand, fine grained, light brown, a little shell fragments (SP)			Lat-Lon 25 42 21.9N 80 05 45.2W  Laboratory Data Depth USCS SpG. 3.5 SP 6.0 SP-SM 7.0 SP-SM 13.5 SM 18.0 SM	2.5
-38.9	8.0		Sand, fine to coarse grained, light brown (SP-SM)				5
-40.9	8.0		Sand, fine to medium grained, some shell fragments, a little shell gravel (SP-SM)				7.5
-44.5	11.6		Silty sand, fine grained, light brown, trace of shell fragments (SM)				10
-52.8	19.9		End of Boring				20
			Soils are field visually classified in accordance with the Unified Soils Classification System.				22.5

THIS FORM REISSUED PREVIOUS EDITIONS ARE OBSOLETE.  
RAN 71

PROJECT  
DADE COUNTY SPP  
01000-G11

HOLE NUMBER  
CB-DAC-179