

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Pensacola Beach-Beach Restoration		10. SIZE AND TYPE OF BIT 4" VIBRACORE		
2. LOCATION (Coordinates or Section) X=1151007.800 Y=482010.200		11. DATUM FOR ELEVATION SHOWN (FSM or MSL) MLLW		
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE		
4. HOLE NO. (As shown on drawing title and file number) P-101		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0		
5. NAME OF DRILLER J. Cole/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -59.1 Ft.		
9. TOTAL DEPTH OF HOLE 20.4 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %		
		19. SIGNATURE OF G. Zarbo, SEA Inc.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LITHO SAMPLE NUMBER	REMARKS
-59.1	0		White fine quartz sand, some shell fragments and whole shells in medium to coarse gravel range, scattered inclusions of decayed organic matter, near zero heavy/dark minerals. 10 YR 8.5/0.5-8.5 (SP)	100	0.5	-59.1
					4.0	
					8.0	-64.1
					12.0	
					16.0	-74.1
-75.0	16.7		White fine quartz sand, abundant coarse shell fragments in medium to coarse gravel range. 10 YR 8/1 (SP)	100		
-79.3	19.2		Gray fine muddy quartz sand, coarse whole shells and shell fragments. 10 YR 8.5/1 (SM)			
-79.5	20.4					-79.5
						Composite 0-18.0 ft.