

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1146012.800 Y=479021.500				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOSIS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) P-104				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0	
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01	
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.4 Ft.	
9. TOTAL DEPTH OF HOLE 19.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF G. Zarillo, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-64.4	0					-64.4
			White fine quartz sand, few inclusions of decayed organic matter, scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 9.25/0.5 (SP)	100	0.5	
					3.0	
						-68.4
-71.3	6.9		White fine quartz sand, few thin layers of crushed shell fragments in fine to medium gravel range. 10 YR 8/1 (SP)	100	7.0	
-72.7	8.3		White fine to very fine quartz sand, few scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 9.25/0.5 (SP)	100	11.0	
						-74.4
-77.5	13.1		White fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 9.25/1 (SP)	100	16.0	
						-78.4
-82.8	18.5		Light gray silty mud, low plasticity. 10 YR 7.5/1 (ML)	100		
-83.7	19.3					-83.7
						Composite 0-17.0 ft.