

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1146387.100 Y=477659.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-108				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -66.0 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-66.0	0		White fine quartz sand, scattered shell fragments in coarse sand to medium gravel range, few large shell fragments. 10 YR 9.25/0.5 (SP)		0.5	-66.0	0
				100	3.0		2.5
-71.5	5.5		White medium to fine quartz sand, trace of shell fragments. 10 YR 9/1 (SP)		6.0	-71.0	5
-73.2	7.2		White fine quartz sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 9.25/0.5 (SP)		10.0		7.5
					10.0	-76.0	10
				100	14.0		12.5
					16.0	-81.0	15
				100	18.0		17.5
-86.3	20.3					-86.3	20
						Composite 0-18.0 ft.	22.5