

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1147235.200 Y=476843.700				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSIS/Disen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-110				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -66.3 Ft.			
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLED ZONES	REMARKS	
-66.3	0		Very pale brown fine quartz sand, near 0% dark/heavy minerals, few large shell fragments and whole shells in medium to coarse gravel range, scattered shell fragments in coarse sand to fine gravel range. 10 YR 7.5/3 (SP)	100	0.5 3.0	-66.3	0
					6.0	-71.3	5
				100	8.0		7.5
					9.0	-76.3	10
-77.2	10.9		White fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 8.5/1 (SP)	100	12.0		12.5
					15.0	-81.3	15
-81.6	15.3		Very pale brown fine quartz sand, few inclusions of decayed organic matter, trace of shell fragments in medium to coarse sand ranges. 10 YR 8/2-8/3 (SP)	100			17.5
						-86.7	20
-86.7	20.4					Composite 0-15.0 ft.	22.5