

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1145522.600 Y=474570.200				11. DATUM FOR ELEVATION SHOWN (TBM or ASL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-113				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -63.1 Ft.			
9. TOTAL DEPTH OF HOLE 17.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, Inc.			

  

ELEV.	DEPTH	LOG	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS
-63.1	0					-63.1
			White medium to fine quartz sand, zero dark/heavy minerals, scattered large shell fragments in coarse gravel range, crushed shell fragments in coarse sand to fine gravel range. 10 YR 9.25/0.5 (SP)	100	0.5	Large Echoid fragment, 0.3 ft.
-65.7	2.6		White medium to fine quartz sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 9.25/0.5 (SP)	100	3.0	
					6.0	-66.1
				100	9.0	
						-73.1
-74.5	11.6		White crushed shell layer mixed with fine quartz sand. range. 10 YR 8/1 (SP)	100	12.0	
			White medium to fine quartz sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 9.25/0.5 (SP)	100	15.0	-78.1
-80.2	17.1					-80.2
						Composite 0-15.0 ft.