

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1142515.300 Y=474557.800				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-119				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-15-01 1-15-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -63.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zorillo, SEA Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG STARTED NUMBER	REMARKS	
-63.0	0		White medium to fine quartz sand, few scattered shell fragments in coarse sand to fine gravel range. 10 YR 8.5/1 (SP)	100	0.5	-63.0	0
-67.6	4.6		White medium to fine quartz sand, trace of shell fragments. 10 YR 9.25/1 (SP)	100	3.0	-68.0	2.5
-74.4	11.4		White medium to fine quartz sand, few large shell fragments and whole shells in coarse gravel range. 10 YR 9.25/0.5 (SP)	100	7.0	-78.0	5
-78.5	15.5			100	11.0	-78.5	7.5
				100	15.0		10
							12.5
							15
							17.5
							20
							22.5
						Composite 0-15.0 ft.	