

Hole No. P-11

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT: 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1117994.300 Y=486361800				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-11				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES: 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN: 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-9-00 9-9-00			
8. DEPTH DRESSED INTO ROCK: 0 Ft.				17. ELEVATION TOP OF HOLE: -36.3 Ft.			
9. TOTAL DEPTH OF HOLE: 20.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING: 100 %			
				19. SIGNATURE OF G. Zarbo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-36.3	0		Light gray to pale brown fine quartz sand, some coarse sand, scattered shell fragments in coarse sand to fine gravel range, near zero heavy/dark minerals. 10 YR 8/2-7/2 (SP)		0.5		0
				100	3.0		2.5
					8.0		5
-44.6	8.3		Gray muddy, fine quartz sand, scattered shell fragments in coarse coarse sand range. 10 YR 5/1 (SM)	100			7.5
-47.1	10.8		Gray plastic mud, scattered wood fragments. 10 YR 5/1 (CL)	100			10
-49.7	13.4		Grayish brown medium to fine quartz sand, high mud content. 10 YR 5/2-5/3 (SM)	100			12.5
				100			15
							17.5
-56.4	20.1						20
							22.5
Composite 0-7.0 ft.							