

Hole No. P-15

DRILLING LOG		DEVIATION		INSTALLATION	
1. PROJECT Pensacola Beach-Beach Restoration				SHEET 1 OF 1	
2. LOCATION (Coordinates or Station) X=118801.300 Y=486075.300				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				11. DATUM FOR ELEVATION SHOWN (TBM or MLLW) MLLW	
4. HOLE NO. (As shown on drawing title and the number) P-15				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
5. NAME OF DRILLER J. Cole/A. Browder				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				14. TOTAL NUMBER OF CORE BOXES 2	
7. THICKNESS OF BURDEN 0 Ft.				15. ELEVATION GROUND WATER	
8. DEPTH DRILLED INTO ROCK 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-9-00 9-9-00	
9. TOTAL DEPTH OF HOLE 20.2 Ft.				17. ELEVATION TOP OF HOLE -42.9 Ft.	
				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF G. ZWING, SEA, INC.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-42.9	0					-42.9
-44.9	2.0		Light gray fine quartz sand, low dark/heavy mineral content, scattered shell fragments, few inclusions of decayed organic matter. 10 YR 7/2 (SP)	100	10	
-46.0	5.1		Dark gray plastic med. inclusions of medium quartz sand. 10 YR 4/1 (CL)	100		-47.9
			Gray medium quartz sand, high med content scattered shell fragments and whole shells in coarse sand to medium gravel range. 10 YR 5/1 (SM)	100		
-55.2	12.3		Gray to light gray medium to coarse sand, scattered shell fragments in fine to medium gravel range. 10 YR 5/2 (SP)	100		-52.9
-57.9	15.0		Light gray to gray medium quartz sand, few scattered shell fragments in fine gravel range. 10 YR 6/1-5/1 (SP)	100		-57.9
-63.1	20.2					-63.1
						No composite.

DWS FORM 1838 PREVIOUS EDITIONS ARE OBSOLETE. MAR 71	PROJECT Pensacola Beach-Beach Restoration	HOLE NUMBER P-15
---	--	---------------------