

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Pinnacles Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1127471.500 Y=483082.300				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOSS/Disen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) P-21				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0	
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-9-00 9-9-00	
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -56.0 Ft.	
9. TOTAL DEPTH OF HOLE 20.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF G. Zarbo, SEA, Inc.	

  

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	W/ SAMPLE NUMBER	REMARKS
-56.0	0		Gray fine quartz sand, near zero shell content. 10 YR 5/1 (SP)			-56.0
				100	0.5	
					2.0	
						-63.0
-64.5	8.5		Gray medium to fine quartz sand, some mud. 10 YR 5/1 (SP)	100	6.0	
						-68.0
-68.7	10.3		Light gray fine quartz sand, inclusions of decayed organic matter, low shell content. 10 YR 7/1-7/2 (SP)	100	10.0	
						-73.0
-73.4	15.4		Light gray to gray fine sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 7/1-6/1 (SP)	100	15.0	
						-76.2
-76.2	20.2			100		
						Composite 0-19.0 ft.