

DRILLING LOG		DIVISION		INSTALLATION		
PROJECT		SHEET 1 OF 1				
Pensacola Beach-Beach Restoration		10. SIZE AND TYPE OF BIT 4" VIBRACORE				
2. LOCATION (Coordinates or Station)		11. DATUM FOR ELEVATION SHOWN (TBM or HSL)				
X=1150002.400 Y=485077.500		MLLW				
3. DRILLING AGENCY		12. MANUFACTURER'S DESIGNATION OF DRILL				
AOS/OSen Associates, Inc.		PNEUMATIC VIBRACORE				
4. HOLE NO. (As shown on drawing title and file number)		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN				
P-29		disturbed: 3 undisturbed: 0				
5. NAME OF DRILLER		14. TOTAL NUMBER OF CORE BOXES				
J. Cole/A. Browder		2				
6. DIRECTION OF HOLE		15. ELEVATION GROUND WATER				
<input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		9-10-00 9-10-00				
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED				
8. DEPTH DRILLED INTO ROCK 0 Ft.		9-10-00 9-10-00				
9. TOTAL DEPTH OF HOLE 20.2 Ft.		17. ELEVATION TOP OF HOLE -85.0 Ft.				
		18. TOTAL CORE RECOVERY FOR BORING 100 %				
		19. SIGNATURE OF G. Zwick, SEA, Inc.				
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-65.0	.0		Light gray fine quartz sand, thin layers of crushed shell in medium sand to fine gravel size range, <1% dark/heavy minerals. 10 YR 7/1-7/2 (SP)	100	0.5	-65.0
-68.2	3.2		Gray to brownish gray fine quartz sand, few % shell fragments in medium to coarse sand size range, scattered whole pelecypod shells to 1 1/4". 10 YR 7/2-7/3 (SP)	100	2.0	-68.2
-68.9	4.9		Gray silty, sandy mud, abundant shell fragments and whole shells to 3/4", thin layers of dark gray plastic mud, scattered inclusions of decayed wood. 10 YR 4/1-5/1 (ML)	100	4.0	-70.0
-75.5	10.5		Dark gray plastic mud inclusions of decayed wood. 10 YR 4/1 (CL)	100		-75.0
-79.4	14.4		Gray medium quartz sand, inclusions of decayed organic matter, <1% dark/heavy minerals. 10 YR 5/1 (SP)	100		-80.0
-85.2	20.2					-85.2
						Composite 0-4.5 ft.