

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1136937.300 Y=466618.900				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY ADSS/Disen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-32				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-10-00 9-10-00			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -57.9 Ft.			
9. TOTAL DEPTH OF HOLE 19.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zullo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-57.9	.0		Light brownish gray fine quartz sand, few scattered shell fragments in medium to coarse sand range. 10 YR 8/1-8/2 (SP)		0.5	-57.9	0
				100	3.0		2.5
-61.6	3.7		Gray to dark gray fine quartz sand, abundant coarse shell fragments and whole shells to 3/4". 10 YR 5/1-4/1 (SP)			-62.9	5
-63.8	5.9		Gray plastic mud mixed with medium quartz sand. 10 YR 5/1 (CL)				7.5
-64.7	6.8		Grayish brown medium quartz sand mixed with mud. 10 YR 5/2-5/3 (SM)	100			10
-67.8	9.9		Light brown to light gray medium quartz sand, few inclusions of decayed organic matter. 10 YR 6/2-6/3 (SP)	100		-72.9	15
				100		-77.1	20
-77.1	19.2						22.5
Composite 0-3.0 ft.							