

DRILLING LOG		DIVISION	INSTALLATION
1. PROJECT Pensacola Beach-Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE
2. LOCATION (Coordinates or Station) X=1084998.800 Y=481014.200			11. DATUM FOR ELEVATION SHOWN (TBM or ASL) MLW
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE
4. HOLE NO. (As shown on drawing title and file number) P-60			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0
5. NAME OF DRILLER J. Cole/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 9-14-00 9-14-00
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -44.4 Ft.
9. TOTAL DEPTH OF HOLE 17.4 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %
			19. SIGNATURE OF S. Zerkow, SEA, Inc.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-44.4	0					-44.4
			White medium to fine quartz sand, near 0% heavy/dark minerals, few scattered inclusions of decayed organic matter. 10 YR 9.25/0.5 (SP)	100	0.5	
					3.0	
						-48.4
				100	6.0	
				100	9.0	
						-54.4
					12.0	
-57.1	12.7		Light gray medium to fine quartz sand, heavy/dark mineral <1%. 10 YR 7.5/1 (SP)	100		Thin layer muddy brown sand, 13.8 ft.
-58.9	14.5		White medium to fine quartz sand, heavy/dark minerals <1%. 10 YR 9.25/0.5 (SP)		15.0	-58.4
-60.5	16.3		Grayish-brown medium to fine sand, some silt. 10 YR 5/1-5/2 (SP)	100		-61.8
-61.8	17.4					
						Composite 0-15.5 ft.