

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=869077.200 Y=494762.300				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-74				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-10-01 1-10-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -52.9 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BONDING 100 %			
19. SIGNATURE OF G. Zarbo, SEA Inc.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-52.9	0		White fine quartz sand, scattered shell fragments in medium to coarse sand range. 10 YR 9.25/1 (SP)		0.5	-52.9	0
-56.2	3.3			100	3.0		2.5
-56.5	3.6		Brown muddy fine quartz sand. 10 YR 8/3 (SM)				
-57.0	4.1		Very light grayish brown fine quartz sand, scattered shell fragments in medium to fine gravel range. 10 YR 8/2 (SP)			-57.9	5
			Brown fine to very fine quartz sand, few scattered shell fragments in fine gravel range. 10 YR 4/3 (SP)	100			7.5
-63.0	10.1					-62.9	10
-63.5	10.6		Brown to dark brown fine silty quartz sand. 10 YR 4/3-3/3 (SM)				
			Grayish brown fine, silty quartz sand, inclusions of decayed organic matter. 10 YR 5/2 (SM)	100			12.5
-66.4	13.5					-67.8	15
			Brown silty fine quartz sand. 10 YR 4/4-5/4 (SM)	100			17.5
-73.2	20.3					-73.2	20
						No composite.	22.5