

<b>DRILLING LOG</b>		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Pensacola Beach-Beach Restoration		10. SIZE AND TYPE OF BIT 4" VIBRACORE		
2. LOCATION (Coordinates or Station) X=173202.000 Y=49182.000		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW		
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE		
4. HOLE NO. (As shown on drawing title and file number) P-75		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0		
5. NAME OF DRILLER J. Cole/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 1-10-01 1-10-01		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -54.0 Ft.		
9. TOTAL DEPTH OF HOLE 20.4 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %		
		19. SIGNATURE OF G. Zaring, SEA Inc.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-54.0	0		White medium to fine quartz sand, scattered shell fragments in coarse sand to medium gravel range, few scattered large whole shells. 10 YR 8.5/0.5 (SP)			-54.0
				0.5		
				100	3.0	
						-58.0
				6.0		
				100	8.0	
						-64.0
-64.0	10.9		Pale brown fine to very fine quartz sand, few scattered shell fragments in coarse sand to medium gravel range. 10 YR 8.5/2 (SP)			
				12.0		
				100		
-68.0	14.8		Grayish brown silty fine sand. 10 YR 5/2 (SM)			-68.0
-69.3	15.3		Gray sandy silt, very low plasticity. 10 YR 5/1 (ML)			
				100		
-74.4	20.4					-74.4
						Composite 0-14.0 ft.