

DRILLING LOG		DIVISION	INSTALLATION
1. PROJECT Pensacola Beach-Beach Restoration			SHEET 1 OF 1
2. LOCATION (Coordinates or Station) X=1154008.900 Y=481114.200			10. SIZE AND TYPE OF BIT 4" VIBRACORE
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			11. DATUM FOR ELEVATION SHOWN (TBW or ASL) M.L.W.
4. HOLE NO. (As shown on drawing title and file number) P-81			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE
5. NAME OF DRILLER J. Cole/A. Browder			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 8 undisturbed: 0
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			14. TOTAL NUMBER OF CORE BOXES 2
7. THICKNESS OF BURDEN 0 Ft.			15. ELEVATION GROUND WATER
8. DEPTH DRILLED INTO ROCK 0 Ft.			16. DATE HOLE STARTED COMPLETED 1-10-01 1-10-01
9. TOTAL DEPTH OF HOLE 20.4 Ft.			17. ELEVATION TOP OF HOLE -58.5 Ft.
			18. TOTAL CORE RECOVERY FOR BORING 100 %
			19. SIGNATURE OF G. Z. #10, SEA Inc.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	CORE W. L. NUMBER	REMARKS	
-58.5	0		White fine quartz sand, scattered shell fragments in fine to coarse gravel range. 10 YR 8/0.5 (SP)		0.5	-58.5	0
-59.0	1.4		White fine quartz sand, few scattered whole shells and shell fragments in medium to coarse gravel range. 10 YR 8.5/0.5 (SP)	100	3.0	Large shell fragments to 2", 1.5-1.8 ft.	2.5
-64.9	6.4		Very light brown fine quartz sand, few scattered shell fragments in fine gravel range. 10 YR 8.5/2 (SP)	100	8.0	-63.5	5
-67.1	8.6		White fine quartz sand, trace of silt, few scattered shell fragments in fine gravel range. 10 YR 8.5/0.5 (SP)		10.0	-68.5	10
-68.8	11.4		Very pale brown fine quartz sand, few scattered shell fragments in fine gravel range. 10 YR 8.5/2 (SP)	100	14.0	-73.5	15
-78.3	19.8		Grayish brown fine quartz sand and large shell fragments, whole shells in medium to coarse gravel range. 10 YR 7.5/0.5 (SP)	100	17.0	-78.2	17.5
-78.2	20.4					Composite 0-17.0 ft.	20
							22.5