

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1138048.100 Y=483891.000				11. DATUM FOR ELEVATION SHOWN (TBM or ASL) M.L.W.			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-84				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -56.0 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zierbo, SEA Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LEG SAMP LE NUM BER	REMARKS	
-56.0	0		White medium to fine quartz sand, zero heavy/dark minerals, few scattered shell fragments in fine gravel range. 10 YR 8/1 (SP)			-56.0	0
				100	0.5		2.5
					4.0		
						-61.0	5
-62.4	6.4		Pale brown medium to fine sand, scattered shell fragments and whole shells in medium to coarse gravel range, few Echinoid fragments. 10 YR 8/3 (SP)	100	8.0		7.5
						-66.0	10
				100	12.0		12.5
-70.2	14.2		Pale brown silty fine sand, abundant large shell fragments and whole shells in coarse gravel range. 10 YR 8/2 (SM)			-71.0	15
-71.8	15.8		Brown silty, sandy mud. 10 YR 4/3 (ML)				
-74.1	18.1		Brown silty mud, very low plasticity. 10 YR 4/3 (ML)	100			17.5
-76.3	20.3					-76.3	20
						Composite 0-13.0 ft.	22.5