

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=143263.100 Y=473566.500				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-68				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -63.1 Ft.			
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC.			
ELEV.	DEPTH	LOG LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-63.1	0		White fine quartz sand, 0% shell and dark minerals, scattered shell fragments. 10 YR 9.25/0.5 (SP)		0.5	-63.1	0
-64.7	1.6		White fine quartz sand, scattered shell fragments and whole shells in medium to coarse gravel range. 10 YR 8.5/1 (SP)	100	3.0		2.5
-66.1	5.0		White fine quartz sand, very few shell fragments and whole shells, 0% heavy/dark minerals. 10 YR 9/0.5 (SP)	100	8.0	-66.1	5
-72.4	9.3		Very light gray fine quartz sand. 10 YR 7.5/2 (SP)		10.0	-73.1	10
-73.2	10.1		White fine quartz sand, zero heavy/dark minerals. 10 YR 9.25/0.5 (SP)	100	13.0		12.5
-77.6	14.5		Light gray fine quartz sand, scattered shell fragments in fine to medium gravel range, near zero heavy/dark minerals. 10 YR 7/1-7.5/1 (SP)	100	17.0	-78.1	15
-83.5	20.4					-83.5	20
						Composite 0-19.0 ft.	22.5