

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Elevations or Station) X=1143486.200 Y=474638.900				11. DATUM FOR ELEVATION SHOWN (TBM or ABL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-89R1				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 7 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS	
-64.0	0					-64.0	0
-65.2	1.2		White medium to fine quartz sand, near 0% heavy/dark minerals. 10 YR 9/2 (SP)		0.5		
			White medium to fine quartz sand, near zero heavy/dark minerals. 10 YR 8.5/0.5 (SP)	100	2.0		2.5
-68.6	5.8				5.0	-68.0	5
			White fine quartz sand, few scattered shell fragments in coarse sand to fine gravel range, 0% heavy/dark minerals. 10 YR 9.25/0.5 (SP)	100	8.0		7.5
-72.5	8.5					-74.0	10
			White medium to fine quartz sand, few large shell fragments, zero heavy/dark minerals. 10 YR 8.5/1 (SP)				
-74.5	10.5				10.0	Large Echinoid fragment, 11.3 ft.	
-75.6	11.8					Large olive shell, 11.7 ft.	12.5
			White medium to fine quartz sand, few scattered shell fragments and whole shells in medium gravel range. 10 YR 8.5/1-9/1 (SP)	100	13.0		
						-78.0	15
-78.9	15.9						
-80.5	18.5		White medium to fine quartz sand. 10 YR 9/0.5 (SP)	100	18.0	-80.5	
							17.5
							20
						Composite 0-18.0 ft.	22.5

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRA-CORE			
2. LOCATION (Coordinates or Station) X=143502.400 Y=474535.100				11. DATUM FOR ELEVATION SHOWN (TBM or ASL) MLLW			
3. DRILLING AGENCY ACSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRA-CORE			
4. HOLE NO. (As shown on drawing title and file number) P-89R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.1 Ft.			
9. TOTAL DEPTH OF HOLE 21.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS	
-64.1	0					-64.1	0
							2.7
							5.4
							8.1
							10.8
-76.1	14.0						13.5
-79.8	15.7		White fine quartz sand, trace of small shell fragments, no heavy/dark minerals. 10 YR 8/0.5 (SP)	100	14.5	-79.1	
-81.2	17.1		White fine quartz sand. 10 YR 8/1 (SP)		17.0		16.2
-82.0	17.9		White fine quartz sand. 10 YR 8.5/0.5 (SP)				
-82.9	18.8		White fine quartz sand. 10 YR 8/1 (SP)	100			18.9
-83.3	19.2		White fine quartz sand. 10 YR 9/1 (SP)				
			White fine quartz sand. 10 YR 8/1 (SP)	20.0			
-85.4	21.3					-85.4	21.8
						Composite 14.0-20.0 ft.	