

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1144298.700 Y=478589.700				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) P-93				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 7 undisturbed: 0	
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01	
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -65.9 Ft.	
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF G. Zaring, SEA Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	WATER SAMPLE NUMBER	REMARKS
-65.9	0		White fine quartz sand, near 0% heavy/dark minerals, scattered shell fragments in fine to medium gravel range. 10 YR 8/1 (SP)	100	0.5	-65.9
					2.0	Large Echinoid frag., 2.7 ft.
					5.0	-70.9
					8.0	-75.9
-75.0	9.1		White fine quartz sand, few shell fragments in fine gravel range. 10 YR 8/1 (SP)	100	12.0	-80.9
-76.1	10.2		Very pale brown fine quartz sand, few scattered shell fragments in fine to coarse gravel range. 10 YR 7.5/3 (SP)	100	15.0	-86.3
					18.0	Composite 0-19.0 ft.
-81.0	15.1		Pale brownish gray fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 7.5/2-7.5/3 (SP)	100		
-86.3	20.4					