

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Persimone Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1166375.400 Y=489056.600				11. DATUM FOR ELEVATION SHOWN (TBM or ASL) MLLW			
3. DRILLING AGENCY ADSS/Disen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-94				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -56.0 Ft.			
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerkle, SEA Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-56.0	0		White medium to fine quartz sand, near 0% heavy/dark minerals, scattered shell fragments in fine to medium gravel range. 10 YR 8.5/0.5 (SP)		0.5		0
				100	3.0		2.5
-61.3	5.3		White medium to fine quartz sand, few shell fragments in fine gravel range. 10 YR 8.5/1 (SP)		6.0		5
				100			7.5
-64.5	8.5		White to very light gray fine quartz sand, few large whole shells. 10 YR 8/0.5 (SP)		9.0		10
							12.5
-67.1	11.1		Light grayish brown fine quartz sand, trace of mud. 10 YR 7.5/1-7.5/3 (SP)				15
-68.2	12.2		Gray fine muddy quartz sand. 10 YR 7/1 (SH)	100			17.5
							20
-71.8	15.9		Gray fine sand, some mud. 10 YR 7/1 (SP)	100			22.5
-75.1	19.1		Gray fine sand and coarse shell fragments, some mud. 10 YR 6.5/1 (SP)				
-76.4	20.4						
						Composite 0-10.0 ft.	