

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Pensacola Beach-Beach Restoration				SHEET 1 OF 1	
2. LOCATION (Coordinates of Station) X=1160497.900 Y=492348.800				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW	
4. HOLE NO. (As shown on drawing title and file number) P-95				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
5. NAME OF DRILLER J. Cole/A. Browder				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				14. TOTAL NUMBER OF CORE BOXES 2	
7. THICKNESS OF BURDEN 0 Ft.				15. ELEVATION GROUND WATER	
8. DEPTH DRILLED INTO ROCK 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01	
9. TOTAL DEPTH OF HOLE 20.2 Ft.				17. ELEVATION TOP OF HOLE -53.1 Ft.	
				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF S. Zwick, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-53.1	0		White medium to fine quartz sand, scattered shell fragments in fine to medium gravel range, trace of decayed organic matter. 10 YR 8/1 (SP)			-53.1
				100	0.5 2.0 4.0	
-58.8	5.8		Light brownish gray fine quartz sand, some silt, near zero carbonate. 10 YR 5/2 (SP)	100		-58.1
-61.2	8.1		Grayish brown fine quartz sand, some silt, no carbonate. 10 YR 4/2 (SP)			
				100		-63.1
-66.6	13.4		Brownish gray silty sand. 10 YR 4/2 (SM)			
				100		-68.1
-73.3	20.2					-73.3
						Composite 0-5.0 ft.