

DRILLING LOG			DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration					10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1158923.300 Y=488756.900					11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY ADSS/Cisen Associates, Inc.					12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-96					13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder					14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED					15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.					16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.					17. ELEVATION TOP OF HOLE -55.1 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.					18. TOTAL CORE RECOVERY FOR BORING 100 %			
					19. SIGNATURE OF G. Zarbo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS		
-55.1	0		White fine quartz sand, trace of shell fragments in medium to coarse sand range and fine gravel range. 10 YR 9.25/0.5 (SP)	100	0.5		0	
					3.0		2.5	
-60.0	4.9		White fine quartz sand, scattered large shell fragments and whole shells in coarse gravel range, shell fragments in coarse sand to fine gravel range. 10 YR 9.25/0.5 (SP)	100	8.0		5	
-62.2	7.1		Light gray fine silty sand, inclusions of dark gray to dark grayish brown decayed organic matter. 10 YR 7.5/1 (SM)	100			7.5	
-64.7	9.6		Light gray silty, fine sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 6.5/0.5 (SM)	100			10	
				100			12.5	
				100			15	
				100			17.5	
-74.0	18.9					Layer of large whole shells, 18.7 ft.		
-75.4	20.3		Light gray fine quartz sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 7.5/0.5 (SP)				20	
						Composite 0-6.0 ft.	22.5	