

<b>DRILLING LOG</b>		DIVISION		INSTALLATION	
1. PROJECT Peracade Beach-Beach Restoration		10. SIZE AND TYPE OF BIT 4" VIBRACORE		SHEET 1 OF 1	
2. LOCATION (Coordinates or Station) X=1153996.000 Y=488000.200		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSIS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-97		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -54.7 Ft.			
9. TOTAL DEPTH OF HOLE 20.1 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %			
		19. SIGNATURE OF G. Zarbo, SEA Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-54.7	0		White fine quartz sand, scattered shell fragments and whole shells in medium gravel range. 10 YR 8.5/0.5 (SP)		0.5	-54.7
-57.0	3.1		Very pale brown fine quartz sand, few scattered shell fragments in fine to medium sand range. 10 YR 8.5/2 (SP)	100	3.0	-57.0
-60.5	5.6		White fine quartz sand, few scattered shell fragments in fine to medium sand range. 10 YR 8.5/0.5 (SP)	100	6.0	-60.5
-62.2	7.5		Pale brown fine quartz sand, some silt, trace of shell fragments. 10 YR 8.5/2 (SP)	100	9.0	-62.2
-65.3	10.6		Grayish brown silty mud, low plasticity. 10 YR 5/2 (ML)	100		-65.3
-74.1	19.4		Gray plastic mud. 10 YR 5/1 (CL)	100		-74.1
-74.6	20.1					-74.6
						Composite 0-9.0 ft.