

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pinnacles Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1152048.400 Y=482173.600				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLM			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and the number) P-102				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -61.3 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarbo, SEA Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	WILSON SAMPLER DEPTH	REMARKS	
-61.3	0		White medium to fine quartz sand, abundant shell fragments and whole shells in medium to coarse gravel range, near zero heavy/dark minerals. 10 YR 8.5/0.5 (SP)	100	0.5	-61.3	0
-63.2	1.9		White medium to fine quartz sand, scattered shell fragments and whole shells in medium to coarse gravel range. 10 YR 9/1 (SP)	100	4.0	-66.3	2.5
-68.4	7.1		White medium to fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 9.25/0.5 (SP)	100	8.0	-71.3	7.5
-72.1	15.8		White fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 8.5/0.5-8.5/1 (SP)	100	12.0	-76.3	12.5
-78.4	17.1		Gray silty, sandy mud, low plasticity, abundant coarse shell fragments. 10 YR 8/1 (ML)	100	16.0	-81.6	17.5
-81.6	20.3						20
						Composite 0-16.0 ft.	22.5