

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates of Station) X=1145024.600 Y=478655.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSIS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-103				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-13-01 1-13-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarbo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NO.	REMARKS	
-64.7	0					-64.7	0
-66.0	1.3		White fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 7.5/1 (SP)		0.5		
			White fine quartz sand, scattered shell fragments in fine gravel range. 10 YR 9.25/0.5 (SP)	100	3.0	1-2" shell fragments, 2.2 ft.	2.5
						-69.7	5
-71.0	6.3		White fine quartz sand, trace of shell fragments. 10 YR 9.25/1 (SP)	100	7.0		7.5
						-74.7	10
-75.8	11.2		White fine quartz sand, trace of shell fragments. 10 YR 9.25/1 (SP)	100	12.0		12.5
-78.1	13.4		White to very pale brown fine quartz sand, trace of shell fragments. 10 YR 9/0.5-9/1.5 (SP)	100	17.0		17.5
-83.3	18.6					-83.3	20
						Composite 0-17.0 ft.	22.5