

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1145149.900 Y=480508.700				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-107				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Bowder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -65.6 Ft.			
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarbo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC. %	SAMPLE NUMBER	REMARKS	
-65.6	0		White fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 9/1 (SP)		05		0
				100	40		2.5
-71.3	5.7		White fine quartz sand, near zero carbonate/shell material. 10 YR 9.25/1 (SP)		80		5
				100	120		7.5
-76.4	10.8		White fine quartz sand, very few shell fragments. 10 YR 9.25/1 (SP)		160		10
				100			12.5
-81.7	16.1		White fine quartz sand, trace of shell fragments. 10 YR 9.25/1 (SP)				15
-82.5	16.9		Very pale brown fine quartz sand, trace of shell fragments, some silt. 10 YR 8.5/1.5 (SP)				17.5
				100			20
-86.0	20.4						22.5
Composite 0-16.0 ft.							