

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates of Station) X=1146232.200 Y=476613.800				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Disen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-109				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -65.4 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARULLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS	
-65.4	0		Very pale brown medium to fine quartz sand, near 0% dark/heavy minerals, few scattered shell fragments in fine to medium gravel range. 10 YR 8/3 (SP)	100	0.5		0
					3.0		2.5
						-70.4	5
-71.3	5.9		White fine quartz sand, very few scattered shell fragments in fine gravel range. 10 YR 9.25/0.5 (SP)	100	6.0		7.5
					9.0		
-75.4	10.0		Very pale brown fine quartz sand, very few shell fragments in fine gravel range. 10 YR 8.5/3 (SP)	100	12.0		10
						-80.4	15
-80.4	15.0		Pale brown fine quartz sand, few scattered shell fragments in coarse sand range, near zero heavy/dark minerals, very few whole shells in coarse gravel range. 10 YR 7/3 (SP)	100	15.0		17.5
						-84.5	20
-84.5	19.1						22.5
Composite 0-15.0 ft.							