

## Hole No. P-10

DRILLING LOG			DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration					10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1114980.500 Y=488518.900					11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.					12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-10					13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder					14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED					15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.					16. DATE HOLE STARTED COMPLETED 9-9-00 9-9-00			
8. DEPTH DRILLED INTO ROCK 0 Ft.					17. ELEVATION TOP OF HOLE -26.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.4 Ft.					18. TOTAL CORE RECOVERY FOR BORING 100 %			
19. SIGNATURE OF G. Zarbo, SEA, Inc.								
ELEV.	DEPTH	LEADER	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	W SAMPLE NUMBER	REMARKS		
-26.0	0					-26.0	0	
-26.6	.6		Brown silty mud, low plasticity. 10 YR 5/3 (ML)					
-28.4	1.4		Gray plastic mud. 10 YR 5/1 (CL)					
			Brown silty, muddy quartz sand. 10 YR 5/3 (SM)	100				
						-33.0	5	
-35.4	7.4		Light gray fine quartz sand, thin layers of decayed organic matter. 10 YR 7/1 (SP)	100		Thin organic layer, 7.1 ft.	7.5	
-37.8	9.8		Gray plastic mud. 10 YR 5/1-5/2 (CL)			-38.0	10	
				100				
						-43.0	15	
				100				
-47.4	19.4					-47.4	20	
						No Composite.	22.5	