

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1145258.800 Y=473557.500				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSIS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-115				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 8 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -63.0 Ft.			
9. TOTAL DEPTH OF HOLE 17.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARULLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMP NUMB	REMARKS	
-63.0	0		Very pale brown medium to fine quartz sand, very few shell fragments, near 0% heavy dark minerals. 10 YR 7.5/3 (SP)			-63.0	0
				100	0.5		2.5
					3.0		
						-68.0	5
					6.0		
-69.9	8.9		Very pale brown medium to fine quartz sand, few scattered shell fragments in medium gravel range. 10 YR 8/3 (SP)	100			7.5
					9.0		
-73.1	10.1		Pale brown to white fine quartz sand. 10 YR 9/1-9/3 (SP)			-73.0	10
					12.0		12.5
-76.1	13.1		Pale brown fine quartz sand, few scattered shell fragments in medium gravel range. 10 YR 7.5/3 (SP)	100			
					15.0	-78.0	15
				100			
-80.6	17.6					-80.6	17.5
							20
							22.5
Composite 0-17.0 ft.							