

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1146241.000 Y=473555.400				11. DATUM FOR ELEVATION SHOWN (FBM or MSL) MLLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-118				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-14-01 1-14-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -63.1 Ft.			
9. TOTAL DEPTH OF HOLE 17.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerbe, SEA Inc.			
ELEV.	DEPTH	LOG	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LEAK SAMPLE NO.	REMARKS	
-63.1	0		White to light gray medium to fine quartz sand, scattered shell fragments in medium to coarse gravel range. 10 YR 7.5/1-8/1 (SP)			-63.1	0
				0.5		Echinoid fragment, 1.5 ft.	
				100			-2.5
-66.4	3.3		White medium to fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 9.25/0.5 (SP)		3.0	-66.1	5
				8.0			
-70.1	7.0		White fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 9.25/0.5 (SP)			-73.1	10
				100			-7.5
				9.0			
				100		-76.1	15
				12.0			-12.5
				15.0		-80.7	17.5
-80.0	16.8		Light gray to pale brown fine quartz sand. 10 YR 7.5/1-7.5/3 (SP)			-80.7	
-80.7	17.8			100			-20
						Composite 0-17.0 ft.	-22.5