

Hole No. P-1

SHEET 1
OF 1

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Parasola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1134961.800 Y=480073.300				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) P-1				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0	
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-8-00 9-8-00	
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -37.7 Ft.	
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %	
				19. SIGNATURE OF B. ZWISG, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-37.7	0					-37.7
-38.6	1.1		Light gray to pale brown medium to fine quartz sand, scattered shell fragments in coarse sand to fine gravel range. 10 YR 8/2 (SP)	100	0.5	
			Light brown fine quartz sand, scattered large shell fragments to 1/4". 10 YR 7/3 (SP)		2.0	
-41.6	3.9					
			Brown to light brown fine muddy quartz sand. 10 YR 8/3-5/3 (SM)			-42.7
-44.3	6.6					
			Gray to dark gray plastic mud. 10 YR 4/1 (CL)	100		-47.7
-50.1	12.4					
			Dark grayish brown muddy fine quartz sand. 10 YR 5/2-4/2 (SM)	100		-52.7
-54.9	17.2					
			Brown fine quartz sand, scattered large whole shells and shell fragments to 1/2". 10 YR 5/3 (SP)	100		-58.7
-58.7	20.4					
						Composite 0-3.5 ft.