

## Hole No. P-22

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Parasola Beach-Beach Restoration		10. SIZE AND TYPE OF BIT 4" VIBRACORE		11. DATUM FOR ELEVATION SHOWN (TBM or AGL) MLW		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
2. LOCATION (Coordinate or Station) X=1163978.200 Y=493988.900		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0		14. TOTAL NUMBER OF CORE BOXES 2		15. ELEVATION GROUND WATER	
3. DRILLING AGENCY AOS/Olsen Associates, Inc.		16. DATE HOLE STARTED COMPLETED 9-10-00 9-10-00		17. ELEVATION TOP OF HOLE -52.2 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %	
4. HOLE NO. (As shown on drawing title and the number) P-22		19. SIGNATURE OF G. Zaris, SEA, Inc.					
5. NAME OF DRILLER J. Cole/A. Brondor							
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED							
7. THICKNESS OF BURDEN 0 Ft.							
8. DEPTH DRILLED INTO ROCK 0 Ft.							
9. TOTAL DEPTH OF HOLE 19.0 Ft.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SCALE	REMARKS	
-52.2	0		Light gray fine quartz sand, no dark/heavy minerals, few whole pelecypod shells to 1", medium shell fragments. 10 YR 7/2 (SP)	100	0.5	-52.2	0
-53.1	0.9		Gray fine sand, heavy/dark mineral content approximately 1%, several large shell fragments to 1-1/2". 10 YR 6/1 (SP)	100	2.0		2.5
-55.4	3.2		Grayish brown fine sand, color mottling with dark gray patches. 10 YR 5/2-4/2 (SP)	100	5.0	-57.2	5
			Gray fine to dark gray very fine sand, some silt. 10 YR 5/1-4/1 (SM)	100	7.0		7.5
-61.3	9.1		Dark grayish-brown very fine muddy sand. 10 YR 4/2-4/3 (SM)	90		-62.2	10
-63.6	11.4		Dark grayish-brown silty, sandy mud, medium to coarse shell fragments. 10 YR 4/2-4/3 (ML)	100			12.5
-65.6	13.4		Brown medium sand mixed with mud, scattered shell fragments in medium to coarse sand size range. 10 YR 4/3 (SM)			-67.2	15
-68.6	16.6		Brown medium sand, some fine sand and mud. 10 YR 5/3 (SP)	100			17.5
-69.3	17.1		Light gray to light brownish gray medium to fine sand. 10 YR 5/2 (SP)			-71.2	20
-71.2	19.0						22.5
Composite 0-8.0 ft.							