

DRILLING LOG		DIVISION	INSTALLATION
1. PROJECT Pensacola Beach, FL-Beach Restoration			SHEET 1 OF 1
2. LOCATION (Coordinates of Station) X=1088619.400 Y=475702.000			10. SIZE AND TYPE OF BIT 4" VIBRACORE
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW
4. HOLE NO. (As shown on drawing title and file number) P-48			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE
5. NAME OF DRILLER J. Cole / A. Browder			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			14. TOTAL NUMBER OF CORE BOXES 2
7. THICKNESS OF BURDEN 0 Ft.			15. ELEVATION GROUND WATER
8. DEPTH DRILLED INTO ROCK 0 Ft.			16. DATE HOLE STARTED COMPLETED 9-13-00 9-13-00
9. TOTAL DEPTH OF HOLE 16.7 Ft.			17. ELEVATION TOP OF HOLE -36.1 Ft.
			18. TOTAL CORE RECOVERY FOR BORING 100 %
			19. SIGNATURE OF G. Zerillo, SEA, Inc.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-36.1	0					-36.1
			White fine quartz sand. 10 YR 8/1 (SP)	100	0.5	
					3.0	
-40.5	4.4		Gray to light gray fine sand. 10 Y 7/1-7/2 (SP)			
-41.4	5.3		White fine quartz sand. 10 YR 9.25/0.5 (SP)		6.0	-41.1
-43.1	7.0		White fine quartz sand. 10 Y 8/1 (SP)	100		Shell fragment 2", 7.0-7.6 ft.
-44.1	8.0		Light gray to pale brown fine quartz sand. 10 YR 7/1-7/3 (SP)		9.0	
-46.3	10.2		White fine quartz sand. 10 YR 9.25/0.5 (SP)	100	12.0	-46.1
					16.0	
-52.6	16.7					-52.6
						Composite 0-16.7 ft.