

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach, FL-Beach Restoration				10. SIZE AND TYPE OF BCT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1088204.800 Y=477005.300				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-49				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole / A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-13-00 9-13-00			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -43.9 Ft.			
9. TOTAL DEPTH OF HOLE 13.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-43.9	0		White fine quartz sand, near zero heavy/dark minerals. 10 YR 9.25/1- 9.25/0.5 (SP)		0.5	-43.9	0
				100	3.0		2.5
-47.6	3.9		White fine quartz sand, heavy/dark minerals less than 1% 10 YR 8/1 (SP)			Decayed organic matter, 4.6-4.9 ft.	
-48.6	4.9		White medium to fine quartz sand, heavy/dark minerals < 1% 10 YR 9.25/0.5 (SP)		6.0	-48.6	5
				100	9.0		7.5
						-53.9	10
				100	12.0		12.5
-55.9	12.0		Very pale brown medium to fine quartz sand, near zero heavy/dark minerals. 10 YR 8/2 (SP)			-55.9	
-56.9	13.0						15
							17.5
							20
						Composite 0-13.0 ft.	22.5