

DRILLING LOG		DIVISION		INSTALLATION		HOLE NO. P-52 SHEET 1 OF 1	
1. PROJECT Pensacola Beach, FL-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1084999.400 Y=477998.360				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-52				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole / A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-14-00 9-14-00			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -35.2 Ft.			
9. TOTAL DEPTH OF HOLE 14.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-35.2	0	[Pattern: Dotted]	Light gray to pale brown medium to fine quartz sand, near zero heavy/dark minerals. 10 YR 7/1-7/3 (SP)	100	0.5	-35.2	0
	3.0				-	2.5	
-40.1	4.9				-40.2	5	
		[Pattern: Dotted]	White to pale brown medium to fine quartz sand, near zero heavy/dark minerals. 10 YR 8/1-8/3 (SP)	100	6.0	-	7.5
					9.0	-	10
-45.6	10.4				-45.2	12.5	
		[Pattern: Dotted]	Very pale brown medium to fine quartz sand, near zero heavy/dark minerals. 10 YR 8/2-8/3 (SP)	100	12.0	-	15
-49.3	14.1				-49.3	17.5	
						20	
						Composite 0-14.0 ft.	22.5

U.S. FORM 1330 PREVIOUS EDITIONS ARE OBSOLETE.

DATE 7/1

PROJECT
Pensacola Beach, FL-Beach Restoration

HOLE NUMBER
P-52