

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1173241.200 Y=497805.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-73				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-10-01 1-10-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -45.4 Ft.			
9. TOTAL DEPTH OF HOLE 18.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarro, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS	
-45.4	0					-45.4	0
-46.1	1		White very fine quartz sand, near zero shell content. 10 YR 9.25/1 (SP)	100	0.5		
-46.4	1.0		Gray very fine sand, some silt. 10 YR 7/1 (SP)				
			White very fine sand, near zero shell content, no heavy/dark minerals. 10 YR 9.25/0.5 (SP)		3.0		2.5
						-50.4	5
-51.7	6.3		Yellowish very fine quartz sand, no carbonate, no shell material. 10 YR 9/2.5 (SP)	100	6.0		7.5
-53.4	8.0		Very light gray to yellowish very fine sand, no carbonate or dark minerals, inclusions of decayed organic matter. 10 YR 8/1-8/3 (SP)				
-54.6	9.2		Light gray very fine quartz sand, no carbonate/shell fragments, inclusions of decayed organic matter, some silt. 10 YR 7.5/1 (SP)	100	10.0	-55.4	10
					14.0		12.5
						-60.4	15
-62.1	16.7		Grayish brown sandy silt, low plasticity. 10 YR 8.5/2-8.5/3 (ML)	100			17.5
-63.6	18.4					-63.6	18.4
							20
							22.5
Composite 0-14.0 ft.							