

DRILLING LOG		DIVISION	INSTALLATION
1. PROJECT Pensacola Beach-Beach Restoration		SHEET 1 OF 1	
2. LOCATION (Coordinates or Station) X=1140039.700 Y=483956.500		10. SIZE AND TYPE OF BIT 4" VIBRACORE	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW	
4. HOLE NO. (As shown on drawing title and file number) P-86		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
5. NAME OF DRILLER J. Cole/A. Browder		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		14. TOTAL NUMBER OF CORE BOXES 2	
7. THICKNESS OF BURDEN 0 Ft.		15. ELEVATION GROUND WATER	
8. DEPTH DRILLED INTO ROCK 0 Ft.		16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01	
9. TOTAL DEPTH OF HOLE 20.4 Ft.		17. ELEVATION TOP OF HOLE -58.9 Ft.	
		18. TOTAL CORE RECOVERY FOR BORING 100 %	
		19. SIGNATURE OF G. Zarillo, SEA Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-58.9	0		White medium to fine quartz sand, zero heavy/dark minerals, scattered shell fragments in medium to fine gravel range, few large Echinoid shell fragments. 10 YR 6.5/0.5 (SP)	100	0.5	-58.9
-63.4	4.5		Very pale brown medium to fine quartz sand, scattered shell fragments in fine to coarse gravel range, scattered large Echinoid fragments. 10 YR 6/2 (SP)	100	4.0	-63.9
-73.1	14.2		Brown muddy fine sand, shell fragments in fine to medium gravel range. 10 YR 5/1 (SM)	100	8.0	-73.9
-76.3	17.4		Pale brown medium to fine sand, few scattered shell fragments in fine gravel range. 10 YR 6.5/3 (SP)	100	12.0	-73.9
-78.3	20.4					-78.3
						Composite 0-13.0 ft.