

## Hole No. P-8

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1133667.500 Y=486670.900				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-8				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 9-8-00 9-8-00			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -50.7 Ft.			
9. TOTAL DEPTH OF HOLE 20.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarno, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-50.7	0		Light gray to pale brown medium quartz sand, heavy/dark minerals near zero, few scattered whole shells & shell fragments 1/4"-r, 10 YR 7/2-7/3 (SP)		0.5		0
				100	3.0		2.5
-55.3	4.6		Brown fine quartz sand, some silt and clay. 10 YR 4/3 (SP)				5
				100	8.0		7.5
-60.8	10.1		Brown fine quartz sand, thin layers of plastic mud, high silt content. 10 YR 4/3 (SM)				10
				100			12.5
-64.6	13.9		White to pale brown medium to fine sand, scattered fragments of lithified sand-rock fragments. 10 YR 8/1-8/3 (SP)				15
				100			17.5
-68.3	16.8		Pale brown medium to fine quartz sand, scattered large rock fragments. 10 YR 7/3 (SP)				20
-70.9	20.2						22.5
						Composite 0-4.0 ft.	