

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=144708.200 Y=475569.600				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and the number) P-91				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 7 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.3 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLING NUMBER	REMARKS	
-64.3	0					-64.3	0
-66.0	1.7		White fine quartz sand, 0% dark/heavy minerals, very few scattered shell fragments in medium gravel range. 10 YR 8.5/1 (SP)		0.5		
			White fine quartz sand, few scattered shell fragments, zero heavy/dark minerals. 10 YR 8.5/1 (SP)	100	3.0		2.5
						-68.3	5
					6.0		
-71.5	7.2		White fine quartz sand, near zero shell content. 10 YR 9/1 (SP)	100			7.5
					9.0		
-74.2	9.9		White fine quartz sand, near zero shell content. 10 YR 9.5/1 (SP)			-74.3	10
				100	12.0		12.5
-79.0	14.7		White fine quartz sand, near zero shell contents. 10 YR 9/1 (SP)			-79.3	15
				100	15.0		
					17.0		17.5
-83.1	16.8		White fine quartz sand. 10 YR 9/1 (SP)				
-84.6	20.3					-84.6	20
						Composite 0-20.0 ft.	22.5