

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Pensacola Beach-Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=145218.300 Y=476837.200				11. DATUM FOR ELEVATION SHOWN (FSH or MLLW) MLLW			
3. DRILLING AGENCY ADSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) P-92				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 7 undisturbed: 0			
5. NAME OF DRILLER J. Cole/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 1-12-01 1-12-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -64.9 Ft.			
9. TOTAL DEPTH OF HOLE 20.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZANILLO, SEA, INC.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-64.9	0					-64.9
			White fine quartz sand, near 0% shell and dark mineral content. 10 YR 9/1 (SP)	100	0.5	
					3.0	
						-69.9
				100	8.0	
-72.8	7.9					
-73.2	8.3		Brown fine quartz sand. 10 YR 7/3 (SP)			
			White fine quartz sand. 10 YR 8.5/1 (SP)		9.0	
-75.2	10.3					-74.9
-76.1	11.2		Pale brown to brown fine quartz sand. 10 YR 8/3-7/3 (SP)			
			White fine quartz sand. 10 YR 8/1-9/1 (SP)	100	12.0	
						-78.8
				100	16.0	
-81.7	16.8		Light grayish brown to brown fine quartz sand, scattered shell fragments and whole shells in fine to coarse gravel range. 10 YR 6/2-6/3 (SP)			
						-85.3
-85.3	20.4					
						Composite 0-20.0 ft.