

DRILLING LOG	DIVISION	INSTALLATION	SHEET 1 OF 1
	1. PROJECT TOWN OF PALM BEACH	10. SIZE AND TYPE OF BIT 3"	
	2. LOCATION (Coordinates or Station) X=974,260 Y=841,507	11. DATUM FOR ELEVATION SHOWN (TBM or MSL) NGVD	
	3. DRILLING AGENCY ALPINE SEISMIC	12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC	
	4. HOLE NO. (As shown on drawing title and file number) VC99-63	13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0	
	5. NAME OF DRILLER ROB SUSKO	14. TOTAL NUMBER OF CORE BOXES 1	
	6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED	15. ELEVATION GROUND WATER	
	7. THICKNESS OF BURDEN 0.0 Ft.	16. DATE HOLE STARTED COMPLETED 4/14/99 4/14/99	
	8. DEPTH DRILLED INTO ROCK 0.0 Ft.	17. ELEVATION TOP OF HOLE -49.9 Ft.	
9. TOTAL DEPTH OF HOLE 19.9 Ft.	18. TOTAL CORE RECOVERY FOR BORING 100 %		
	19. SIGNATURE OF GEOLOGIST L. DALESSIO		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-49.9	.0					-49.9
		SAND, light gray fine with 5-10% shell and coral fragments (SP) 0.15" coral fragment @ 3.1'			#1	Sample #1, Depth = 3.5' 0.13 mm, 0.53 phi sorting 1.7% silt
					#2	Sample #2, Depth = 9.0' 0.13 mm, 0.69 phi sorting 2.5% silt
					#3	Sample #3, Depth = 14.0' 0.13 mm, 0.66 phi sorting 2.5% silt
-69.8	19.9					
			NOTES: 1. Soils are visually classified in accordance with the Unified Soils Classification System.			