

DRILLING LOG		DIVISION SOUTH ATLANTIC		INSTALLATION JACKSONVILLE DISTRICT		Hole No. CB-MC99-3	
1. PROJECT MARTIN COUNTY				10. SIZE AND TYPE OF BIT 4" dia. Vibracore			
2. LOCATION <i>Coordinates of Station</i> X 776763 Y 1043859				11. DATUM FOR ELEVATION SHOWN ON MLLW			
3. DRILLING AGENCY WILMINGTON DISTRICT				12. MANUFACTURER'S DESIGNATION OF DRILL VIBRA-CORE (SNELL)			
4. HOLE NO. As shown on drawing 1838 and file number CB-MC99-3				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 2			
5. NAME OF DRILLER JERRY FULCHER CRANE OPERATOR				14. TOTAL NUMBER CORE BOXES N/A			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEC. FROM VERT.				15. ELEVATION GROUND WATER N/A			
7. THICKNESS OF OVERBURDEN N/A				16. DATE HOLE STARTED 08/25/99 COMPLETED 08/25/99			
8. DEPTH DRILLED INTO ROCK 0.0'				17. ELEVATION TOP OF HOLE -24.4' MLLW			
9. TOTAL DEPTH OF HOLE 16.0'				18. TOTAL CORE RECOVERY FOR BORING N/A			
				19. SIGNATURE OF INSPECTOR Bob Keistler, PE			
ELEVATION MLLW	DEPTH feet	LEGEND	CLASSIFICATION OF MATERIALS (Designation)	% CORE RECOVERY	BOX OR SAMPLE NO.	REMARKS (Drilling time, water level, depth of weathering, etc., if significant)	
-24.4	0		SAND - poorly graded SILTY, FINE TO MEDIUM GRAY, WITH shell fragments (SP-SM)		1	Time Begin Vibracoring: 11.00 hrs. Soils field classified by Larry Benjamin, Civil Engineer Technician	
	2						
	4						
	6		6.0' TRACE OF SHELL FRAGMENTS		2		
	8						
-32.8	8.4		8.4' ASSUMED NOT RECOVERED				
	10						
	12						
	14						
-40.4	16		BOTTOM OF HOLE AT 16.0' SOILS ARE FIELD VISUALLY CLASSIFIED IN ACCORDANCE WITH THE UNIFIED SOIL CLASSIFICATION SYSTEM				

PRELIMINARY