

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Palm Beach County Vibracore 2004 Palm Beach County, Florida			9. SIZE AND TYPE OF BIT 4.0 In.	
2. BORING DESIGNATION BB04-32			10. COORDINATE SYSTEM/DATUM Florida State Plane East	
3. DRILLING AGENCY Alpine OSS, Inc.			11. MANUFACTURER'S DESIGNATION OF DRILL Alpine Pneumatic Vibracore	
4. NAME OF DRILLER SEA INC			12. TOTAL SAMPLES 5	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			13. TOTAL NUMBER CORE BOXES 2	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			14. ELEVATION GROUND WATER	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			15. DATE BORING 05-25-04	
8. TOTAL DEPTH OF BORING 19.1 Ft.			16. ELEVATION TOP OF BORING -24.6 Ft.	
			17. TOTAL RECOVERY FOR BORING 19.1 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR Gary Zarillo PG	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	REMARKS
-24.6	0.0					
			Light gray (10YR-7/1), Gray medium to fine carbonate sand, gray fine quartz sand, (SP).		1.0	Sample #1.0, Depth = 1.0
					5.0	Sample #5.0, Depth = 5.0
-30.7	6.1		Light gray (10YR-7/1), Gray coarse to fine carbonate sand, fine gray quartz sand, abundant gray whole shells and shell fragments in fine to coarse gravel range, (SP).		8.0	Sample #8.0, Depth = 8.0
-33.3	8.7				12.0	Sample #12.0, Depth = 12.0
			Light gray (10YR-7/1), Gray medium to fine carbonate sand, fine gray quartz sand, scattered light gray shell fragments in coarse sand to fine gravel range, (SP).		16.0	Sample #16.0, Depth = 16.0
-42.8	18.2					
-43.7	19.1		Light gray (10YR-7/1), Gray to tannish gray coarse to fine carbonate sand, fine quartz sand, shell fragments in fine gravel range, (SP).			Sample #Comp, Depth = 19.0
			End of Boring		Comp	Composite 0-17.0 ft.