

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT South Amelia Island Shoreline Stabilization				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=371016.700 Y=2244775.700				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) A-25				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 6 undisturbed: 0			
5. NAME OF DRILLER C. Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 4-16-01 4-19-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -6.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-6.1	.0					-6.1	0
-7.4	1.3		White fine quartz sand, abundant pale brown shell fragments and whole shells in fine to medium gravel range. 10 YR 8.5/0.5 (SP)		0.5		
-9.2	3.1		Very light gray fine quartz sand, scattered pale brown shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	3.0		2.5
			Very pale brown to white fine quartz sand, few scattered gray to pale brown shell fragments and whole shells in fine to medium gravel range. 10 YR 8.5/0.5-8.5/2 (SP)			-11.1	5
					6.0		
				100			7.5
					10.0	-16.1	10
				100			12.5
-20.2	14.1				14.0		
			Very light gray fine quartz sand, abundant inclusions and thin layers of gray plastic mud, scattered gray shell fragments and whole shells in fine to medium gravel range. 10 YR 7.5/0.5 (SP)			-21.1	15
				100	18.0		17.5
-25.9	19.8					-25.9	20
						Composite 0-18.0 ft.	22.5