

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT Walton County Borrow Area A Walton County, Florida				9. SIZE AND TYPE OF BIT			
2. BORING DESIGNATION WA-2				LOCATION COORDINATES X = 1,385,538 Y = 480,747		10. COORDINATE SYSTEM/DATUM Florida State Plane North	
3. DRILLING AGENCY				CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibrocure	
4. NAME OF DRILLER Alpine				12. TOTAL SAMPLES		13. TOTAL NUMBER CORE BOXES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				DEG. FROM VERTICAL		BEARING	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				14. ELEVATION GROUND WATER		15. DATE BORING 08-23-06 17:38	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -69.5 Ft.		17. TOTAL RECOVERY FOR BORING 19.9 Ft.	
8. TOTAL DEPTH OF BORING 19.2 Ft.				18. SIGNATURE AND TITLE OF INSPECTOR		COMPLETED 08-23-06 17:40	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-69.5	0.0					
					WA-2 0'	Sample #WA-2 0', Depth = 0.0'
					WA-2 1.5'	Sample #WA-2 1.5', Depth = 1.5'
					WA-2 3.0'	Sample #WA-2 3.0', Depth = 3.0'
					WA-2 4.5'	Sample #WA-2 4.5', Depth = 4.5'
					WA-2 6.0'	Sample #WA-2 6.0', Depth = 6.0'
			Carbonate-cemented sediment. Medium sand. Scattered mud-filled burrows could be seen from depth of 2.9' to 3.3', and 4.3' to 4.7'. Scattered shells was found from depth of 5.6' to 6.2'. (SP).			
-85.2	15.7					
-85.3	15.8		Peat., (PT).			
			Medium sand, with scattered mud-filled burrows. A small piece of wood was found at the bottom., (SP).			
-89.4	19.9					
			End of Boring			

FLORIDA DEP ROSS WALTON COUNTY DETAIL PHASE II.GPJ FL DEP ROSS.GDT 09/12/07