

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Walton County Borrow Area A Walton County, Florida			9. SIZE AND TYPE OF BIT	
2. BORING DESIGNATION WA-45			10. COORDINATE SYSTEM/DATUM Florida State Plane North	
LOCATION COORDINATES X = 1,379,953 Y = 479,975			HORIZONTAL NAD 1983	
3. DRILLING AGENCY			11. MANUFACTURER'S DESIGNATION OF DRILL Vibrocure	
CONTRACTOR FILE NO.			<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER Alpine			12. TOTAL SAMPLES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			DISTURBED	
DEG. FROM VERTICAL			UNDISTURBED (UD)	
BEARING			13. TOTAL NUMBER CORE BOXES	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			14. ELEVATION GROUND WATER	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			15. DATE BORING 08-27-06 09:55	
8. TOTAL DEPTH OF BORING 19.3 Ft.			STARTED 08-27-06 09:55	
			COMPLETED 08-27-06 09:59	
			16. ELEVATION TOP OF BORING -69.0 Ft.	
			17. TOTAL RECOVERY FOR BORING 15.9 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-69.0	0.0					
					WA-45 0'	Sample #WA-45 0', Depth = 0.0'
					WA-45 1.5'	Sample #WA-45 1.5', Depth = 1.5'
					WA-45 3.0'	Sample #WA-45 3.0', Depth = 3.0'
					WA-45 4.5'	Sample #WA-45 4.5', Depth = 4.5'
					WA-45 6.0'	Sample #WA-45 6.0', Depth = 6.0'
					WA-45 7.5'	Sample #WA-45 7.5', Depth = 7.5'
					WA-45 9.0'	Sample #WA-45 9.0', Depth = 9.0'
-77.6	8.6		Medium sand. Scattered burrows at 4' to 4.8', and mud-filled burrows at 7.3' to 8.6'. Shells at 0' to 3.0', (SP).			
-79.6	10.6		Fine sand. Mud-filled burrows at 8.6' to 9.4', shells at 9.3' to 9.6', and 10.4' to 10.5', (SP).			
-85.1	16.1		Carbonate-cemented sediment. A few shells at 13.7' to 13.8'..			
			End of Boring			

FLORIDA DEP ROSS WALTON COUNTY DETAIL PHASE II.GPJ FL DEP ROSS.GDT 09/12/07