

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT Walton County Borrow Area A Walton County, Florida				9. SIZE AND TYPE OF BIT			
2. BORING DESIGNATION WA-33				LOCATION COORDINATES X = 1,379,025 Y = 474,496		10. COORDINATE SYSTEM/DATUM Florida State Plane North	
3. DRILLING AGENCY				CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibracore	
4. NAME OF DRILLER Alpine				12. TOTAL SAMPLES		13. TOTAL NUMBER CORE BOXES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				DEG. FROM VERTICAL		BEARING	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				14. ELEVATION GROUND WATER		15. DATE BORING 08-28-06 10:16	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -75.2 Ft.		17. TOTAL RECOVERY FOR BORING 19.8 Ft.	
8. TOTAL DEPTH OF BORING 1.0 Ft.				18. SIGNATURE AND TITLE OF INSPECTOR		19. COMPLETED 08-28-06 10:18	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-75.2	0.0					
-79.5	4.3		Medium sand, with scattered burrows at the lower section. Shells at 0' to 2.1', (SP).		WA-33 0' WA-33 1.5' WA-33 3.0'	Sample #WA-33 0', Depth = 0.0' Sample #WA-33 1.5', Depth = 1.5' Sample #WA-33 3.0', Depth = 3.0'
-89.0	13.8		Medium sand, with abundant mud-filled burrows at 4.3' to 13.8'. Shells at 4.3' to 4.6'. Small piece of wood at 5.8' to 6.0', and scattered organics at 9.0' to 9.5', (SP).			
-91.1	15.9		Fine sand, with scattered mud-filled burrows., (SP).			
-93.7	18.5		Medium sand. Shells at the top of this layer., (SP).			
-95.0	19.8		Coarse sand, with scattered organics at 19.7' to 19.7', (SP).			
			End of Boring			

FLORIDA DEP ROSS WALTON COUNTY DETAIL PHASE II.GPJ FL DEP ROSS.GDT 09/12/07