

<b>DRILLING LOG</b>		<b>DIVISION</b>	<b>INSTALLATION</b>	<b>SHEET 1</b> <b>OF 1 SHEETS</b>
<b>1. PROJECT</b> Walton County Borrow Area A Walton County, Florida			<b>9. SIZE AND TYPE OF BIT</b>	
<b>2. BORING DESIGNATION</b> WA-40			<b>10. COORDINATE SYSTEM/DATUM</b> Florida State Plane North	
<b>LOCATION COORDINATES</b> X = 1,373,958 Y = 474,390			<b>HORIZONTAL</b> NAD 1983	
<b>3. DRILLING AGENCY</b>			<b>11. MANUFACTURER'S DESIGNATION OF DRILL</b> Vibrocure	
<b>CONTRACTOR FILE NO.</b>			<input type="checkbox"/> <b>AUTO HAMMER</b> <input type="checkbox"/> <b>MANUAL HAMMER</b>	
<b>4. NAME OF DRILLER</b> Alpine			<b>12. TOTAL SAMPLES</b>	
<b>5. DIRECTION OF BORING</b> <input checked="" type="checkbox"/> <b>VERTICAL</b> <input type="checkbox"/> <b>INCLINED</b>			<b>13. TOTAL NUMBER CORE BOXES</b>	
<b>DEG. FROM VERTICAL</b>			<b>14. ELEVATION GROUND WATER</b>	
<b>BEARING</b>			<b>15. DATE BORING</b> 08-27-06 14:37	
<b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.			<b>16. ELEVATION TOP OF BORING</b> -70.4 Ft.	
<b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.			<b>17. TOTAL RECOVERY FOR BORING</b> 18 Ft.	
<b>8. TOTAL DEPTH OF BORING</b> 17.4 Ft.			<b>18. SIGNATURE AND TITLE OF INSPECTOR</b>	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-70.4	0.0					
					WA-40 0'	Sample #WA-40 0', Depth = 0.0'
					WA-40 1.5'	Sample #WA-40 1.5', Depth = 1.5'
					WA-40 3.0'	Sample #WA-40 3.0', Depth = 3.0'
					WA-40 4.5'	Sample #WA-40 4.5', Depth = 4.5'
					WA-40 6.0'	Sample #WA-40 6.0', Depth = 6.0'
-77.4	7.0		Medium sand. Scattered burrows at 3.9' to 5.5'. Shells at 0' to 3.3', and 5' to 7'. (SP).		WA-40 7.5'	Sample #WA-40 7.5', Depth = 7.5'
-78.5	8.1		Fine sand, with scattered shells. Scattered burrows at bottom., (SP).		WA-40 9.0'	Sample #WA-40 9.0', Depth = 9.0'
-80.6	10.2		Medium sand, with scattered shells. Broows at bottom., (SP).		WA-40 10.5'	Sample #WA-40 10.5', Depth = 10.5'
					WA-40 12.0'	Sample #WA-40 12.0', Depth = 12.0'
-84.4	14.0		Fine sand. A whole shell at 11.2', 12.5', and a big whole shell at 11.7'. (SP).			
-87.9	17.5		Fine sand, with lenticular medium sands. Shells at depth of 16' to 17'. (SP).			
-88.4	18.0		Carbonate-cemented sediment..			
			End of Boring			

FLORIDA DEP ROSS WALTON COUNTY DETAIL PHASE II.GPJ FL DEP ROSS.GDT 09/12/07