

Boring Designation HI-V1

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Humiston & Moore, Honeymoon Island Dunedin, FL			9. SIZE AND TYPE OF BIT 3.0 In.	
2. BORING DESIGNATION HI-V1			10. COORDINATE SYSTEM/DATUM Florida State Plane West	
3. DRILLING AGENCY Athena Technologies			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER P. McClellan			12. TOTAL SAMPLES 2	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			13. TOTAL NUMBER CORE BOXES	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			14. WATER DEPTH 6.4 Ft.	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			15. DATE BORING 01-27-10 13:53	
8. TOTAL DEPTH OF BORING 8.0 Ft.			16. ELEVATION TOP OF BORING -8.22 Ft.	
			17. TOTAL RECOVERY FOR BORING 7.08 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR A. Freeze	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations corrected for either expansion or compaction based on judgement	% REC.	BOX OR SAMPLE	REMARKS
-8.2	0.0					
-11.9	3.6		Fine quartz SAND, little carbonate material, trace silt, subround, poorly graded, very loose, few: carbonate shells >20mm, burrows, grades to light gray (2.5Y 7/1) from, light gray (2.5Y-7/2), (SP).		HI-V1-1	Sample #HI-V1-1, Depth = 3.6' Mean (mm): 0.29, Phi Sorting: 1.64 Fines (230): 2.21% (SP) 17.2% Carbonate
-14.4	6.1		Fine quartz SAND, trace silt/carbonate material, subround, poorly graded, very loose, few: burrows, flaser beds, 4.2' + 4.4'= carbonate % increase, 5.1'= flaser bed, white (5Y-8/1), (SP).		HI-V1-2	Sample #HI-V1-2, Depth = 6.1' Mean (mm): 0.19, Phi Sorting: 0.75 Fines (230): 1.35% (SP)
-14.7	6.5		Fine quartz SAND, little silt, trace carbonate material, subround, poorly graded, loose, bioturbated, very dark gray (5Y-3/1), (SP-SM).			
-15.3	7.1		Cemented LIMESTONE, dense, light gray (5Y-7/1).			
			End of Boring			

FLORIDA DEP ROSS HONEYMOON GINT LOGS.GPJ FL DEP ROSS.GDT 3/12/10